

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/044097

International filing date: 11 December 2004 (11.12.2004)

Document type: Certified copy of priority document


Document details: Country/Office: US
Number: 60/544,702
Filing date: 12 February 2004 (12.02.2004)

Date of receipt at the International Bureau: 31 March 2005 (31.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 22, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/544,702

FILING DATE: *February 12, 2004*

RELATED PCT APPLICATION NUMBER: PCT/US04/44097



Certified by

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. **EL 753209174 US**U.S. PTO
601544702

021204

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
David		Okada		Chandler, AZ	
Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
METAL SYSTEM FOR DIRECT DIE ATTACHMENT					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input checked="" type="checkbox"/> Customer Number:		24964			
OR					
<input type="checkbox"/> Firm or Individual Name					
Address					
Address					
City		State		Zip	
Country		Telephone		Fax	
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		6		<input type="checkbox"/> CD(s), Number _____	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets		4		<input type="checkbox"/> Other (specify) _____	
<input type="checkbox"/> Application Date Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE Amount (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees.				\$80.00	
<input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: 06-0923					
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

[Page 1 of 2]

Date February 12, 2004

SIGNATURE

William C. Hwang

REGISTRATION NO. 36,169

(if appropriate)

TYPED OR PRINTED NAME William C. Hwang

Docket Number: 104023-679-PRO

TELEPHONE (212) 813-8815

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Country: US
Application No.: TBA
Filing Date: February 12, 2004
Inventors: David Okada
Title: METAL SYSTEM FOR DIRECT DIE ATTACHMENT
Atty Docket No.: 104023-679-PRO

CERTIFICATE OF "EXPRESS MAILING"

"EXPRESS MAIL" Mailing Label Number: EL 753209174 US


Deposited: February 12, 2004

I hereby certify that this and the enclosed paper(s) and/or fee(s) is/are being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated above and is addressed to: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Submitted herewith are the following items:

1. Provisional Application For Patent Cover Sheet (in duplicate) (2 pages);
2. Provisional Application of David Okada (10 pages);
3. This Certificate of Express Mailing bearing Express Mailing Label No. and deposit date stated above (1 page); and
4. Return Receipt Postcard.

TOTAL PAGES IN THIS SUBMISSION: 13 + postcard



Francene Sawyer

CERTIFICATE OF EXPRESS MAILING

EXPRESS MAIL Mailing Label Number: EL 753209174 US

Date of Deposit February 12, 2004

I hereby certify that this correspondence, fee, and all accompanying papers, if any, are being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.



February 12, 2004

Francene Sawyer

Date

U.S. Provisional Patent Application Entitled

METAL SYSTEM FOR DIRECT DIE ATTACHMENT

Inventor:

David Okada, 5681 W Park Ave., Chandler, AZ 85226

TITLE

[0001] METAL SYSTEM FOR DIRECT DIE ATTACHMENT

FIELD OF THE INVENTION

[0002] This invention generally relates to a system for mounting semiconductor

5 dies on a circuit board.

BACKGROUND OF THE INVENTION

[0003] A typical surface mountable semiconductor components consists of a semiconductor die attached to a lead frame, wire bonded, and encapsulated into a plastic

package with exposed leads. Soldering the leads to the printed circuit board provides

10 mechanical, thermal, and electrical connections to the semiconductor die.

[0004] Figure 1 shows a typical wire bonded die. Wire bonds add parasitic

inductance and series resistance to the electronic component/circuit. The added inductance and resistance is undesirable for many devices, including high frequency

devices, high speed devices, and low on-resistance power semiconductor devices. The

15 lead frame provides the primary thermal conduction path for the die. The length of the

thermal path to the printed circuit board and lead frame design and composition limits the thermal performance of a package.

[0005] Wire bonds and lead frames can be eliminated using flip chip wafer

bumping packaging. Examples of two available flip chip processes are shown in Figure

20 2. Additional processing is performed to the top surface of the semiconductor die 210 to attach a solder ball 220 or build a raised conductive region which may be made of silicon or a metallic material such as copper, nickel or other metal or alloy, with a top coating of solder. The processing creates a conductive region 260 that allows solder ball 220 or

another conductive region to electrically contact silicon die 210. This allows the device to be attached to the printed circuit board. A disadvantage of the solder ball approach is the limited contact area of the ball to the die surface and printed circuit board. This reduces both the thermal and electrical conduction areas increasing both the thermal and electrical resistance. The thermal and electrical paths are long, approximately the diameter of the solder ball. The limited contact area of the ball also results in the limited mechanical strength of the bond between the die and printed circuit board.

[0006] The copper pedestal bump using pillar 230 is an improvement over the solder ball. Current and heat flows through copper which is significantly more thermally and electrically conductive than solder. The standard height of pillar 230 (approx. 100um) adds to both the thermal and electrical resistance. Both bumping processes involve multiple processing steps and require specialized equipment which adds cost.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The figures below depict various aspects and features of the present invention in accordance with the teachings herein.

DESCRIPTION OF THE INVENTION

[0008] The aspects, features and advantages of the present invention will become better understood with regard to the following description with reference to the accompanying drawings. What follows are preferred embodiments of the present invention. It should be apparent to those skilled in the art that the foregoing is illustrative only and not limiting, having been presented by way of example only. All the features disclosed in this description may be replaced by alternative features serving the same purpose, and equivalents or similar purpose, unless expressly stated otherwise. Therefore,

numerous other embodiments of the modifications thereof are contemplated as falling within the scope of the present invention as defined herein and equivalents thereto. Use of absolute terms, such as “will not,” “will,” “shall,” “shall not,” “must,” and “must not,” are not meant to limit the present invention as the embodiments disclosed herein are
5 merely exemplary.

[0009] The present invention is applicable to all types of semiconductor die, such as integrated circuits, discrete semiconductor devices, sensors, micro-machined structures, etc. -- one aspect of the present invention disclosed here is shown in Figure 3.

[0010] In particular, solderable metal contact regions 310 are formed directly
10 onto the top metal surface 320 of die 300. The solderable metal regions 310 allows die 300 to be directly soldered onto a printed circuit board. Advantages of this system is that it requires only the deposition and patterning of thin metal film layers on the order of 1um thick onto solderable metal regions 310. Examples of solderable films are TiCu, TiNiAg, or AlNiVCu. These films can be used alone or covered with a top layer of
15 solder. The solder layer will help to prevent oxidation of the exposed metal and may simplify mounting to the printed circuit board.

[0011] An illustration of a die mounted onto the printed circuit board is shown in Figure 4. In particular, the die with a solderable metal system can be mounted to the printed circuit board 430 using conventional surface mount techniques. A thin layer of
20 solder paste 410 can be deposited with a stencil onto the printed circuit board 430. The die 300 is then placed into the proper location and lowered until it is in contact with paste 410. The printed circuit board 430 assembly is then heated to approximately 200C until the solder reflows. The solderable metal patterns on the die are then directly soldered to

the copper printed circuit board traces 420 thereby forming a mechanical, electrical, and thermal connection.

[0012] If the optional solder layer is added to the solderable metal system, it is not necessary to apply the solder paste 410. The solder on the die, once reflowed, will be sufficient to attach the die to the printed circuit board, further simplifying the assembly process.

[0013] Advantages of this invention are summarized as follows:

- Simplicity of the packaging
- Ease of manufacturing
- Simplicity of mounting device to the printed circuit board
- Enhanced thermal performance of the package.
- Very short thermal path from the semiconductor die to the printed circuit board.
- Contact areas can be maximized to increase area of thermal path
- thereby reducing the thermal resistance
- Very low electrical resistance from die surface to the printed circuit board.
- Short current path from die to printed circuit board.
- Contact areas can be increase to further minimize the series resistance.
- No wire bond or lead frame inductance and resistance.

CONCLUSION

[0014] Having now described preferred embodiments of the invention, it should be apparent to those skilled in the art that the foregoing is illustrative only and not limiting, having been presented by way of example only. All the features disclosed in

this specification (including any accompanying claims, abstract, and drawings) may be replaced by alternative features serving the same purpose, and equivalents or similar purpose, unless expressly stated otherwise. Therefore, numerous other embodiments of the modifications thereof are contemplated as falling within the scope of the present
5 invention as defined by the appended claims and equivalents thereto.

Semiconductor Die with Solderable Metal System Allowing Direct Surface Mounting to Printed Circuit Boards




Figure 1. Example of Wire Bonding Used to Form the Electrical Connections to the Semiconductor Die

Semiconductor Die with Solderable Metal System Allowing Direct Surface Mounting to Printed Circuit Boards





Figure 2. Typical Flip Chip Wafer Bumping Packages

Semiconductor Die with Solderable Metal System Allowing Direct Surface Mounting to Printed Circuit Boards



Solderable Metal Contact Region 310



Top Metal Layer 320 of Die



Passivation Layer 330

Figure 3. Die with Solderable Metal Contacts for Direct Printed Circuit Board Mounting

Semiconductor Die with Solderable Metal System Allowing Direct Surface Mounting to Printed Circuit Boards




Figure 4. Illustration of Die with Solderable Electrical Contacts Mounted on Printed Circuit Board

- ☐ Solderable Metal Contact Region 310
- ☐ Solder
- ☒ Copper Printed Circuit Board Traces 420
- ☐ Printed Circuit Board 430